




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : B07B 1/46, B29C 70/70, 33/40		A1	(11) International Publication Number: <b>WO 98/37988</b>
			(43) International Publication Date: 3 September 1998 (03.09.98)
(21) International Application Number: PCT/GB98/0060		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 25 February 1998 (25.02.98)			
(30) Priority Data: 9704332.7 1 March 1997 (01.03.97) GB 9719850.1 19 September 1997 (19.09.97) GB			
(71) Applicant (for all designated States except US): UNITED WIRE LIMITED [GB/GB]; Granton Park Avenue, Edinburgh EH5 1HT (GB).			
(72) Inventors; and (75) Inventors/Applicants (for US only): COOK, Gordon, James [GB/GB]; 6 St. Nathans Road, Newtonhill, Kincardineshire AB3 2SW (GB). HUGHES, Andrew [GB/GB]; 6 Davison Park, Edinburgh EH4 2PF (GB). BAILEY, Arthur, Robert [GB/GB]; 81 Little Sutton Lane, Sutton Coldfield, West Midlands B75 6SJ (GB). HARTNUP, George, Charles [GB/GB]; Catcane House, Gorebridge EH23 4QF (GB). STEWART, Dugald [GB/GB]; 69 Fox Covert Avenue, Edinburgh EH12 6UH (GB).			
(74) Agent: KEITH W. NASH & CO.; 90-92 Regent Street, Cambridge CB2 1DP (GB).		Published With international search report. — Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: IMPROVED FILTERING SCREEN AND SUPPORT FRAME THEREFOR



## (57) Abstract

A method of constructing a frame (10) for a filtering screen from a polymer material is described in which a wire frame reinforcement is wholly encapsulated during the frame moulding process so that two parallel spaced apart wires extend through each of the intersecting orthogonal ribs (14, 16) which define the open area of the frame (10) across which the wirecloths (158, 159) are stretched. The surfaces of the frame (10) in which the wirecloths (158, 159) are embedded are formed with ridges (22, 30, 32) and the crests of the latter extend to different heights. The crests are softened by heating during the manufacturing process and the wirecloths (158, 159) stretched over the frame (10) are forced into the softened crests after which the assembly is allowed to cool and cure. The frame (10) is re-usable by stripping wirecloths (158, 159) from the top of the frame (10) and fitting fresh wirecloths over the plastics material and heating the regions which are to encapsulate the fresh wirecloth.